

Product Reference Guide

800 548 3534 | customerservice@blatchfordus.com

Blatchford

	Product	Activity Level	Suggested L-Code ⁸	Weight Rating	Build Height	Envir.	Warranty (months)	Component Weight ¹	Order Code Builder						
									Part Number	Size (cm)	Side	Width ²	Spring Set	Axial Spring	Foot Shell ³
Integrated Limb System		Linx	 L5828 ✓ L5845 ✓ L5848 ✓ L5856 ✓ L5973 ✓	125kg 275lbs	470-565mm 18½"-26¾"		36	2.6kg 5lb 12oz	LINX	22-30	L / R	N / W	1-8		S
Microprocessor Ankles		Elan	 L5973 ✓	125kg 275lbs	170-175mm 6⅜"-6⅞"		36	920g 2lb	ELAN	22-30	L / R	N / W	1-8		S
		Elan ^{IC}	 L5973 ✓	125kg 275lbs	172-177mm 6¾"-6⅞"		36	1kg 2.2lb	ELANIC	22-30	L / R	N / W	1-8		S
Hydraulic Ankles		Echelon ^{VT}	 L5981 L5968 L5988	125kg 275lbs	168-178mm 6⅝"-7"		36	855g 1lb 14oz	ECVT	22-30	L / R	N / W	1-8	1-4	S
		Echelon ^{VAC}	 L5981 L5968 L5781	125kg 275lbs	121-131mm 4¾"-5⅞"		36	700g 1lb 9oz	EVAC	22-30	L / R	N / W	1-8		S
		Echelon	 L5981 ✓ L5968 ✓	125kg 275lbs	115-125mm 4⅞"-4⅝⅞"		36	688g 1lb 8oz	EC	22-30	L / R	N / W	1-8		S
		Echelon ^{ER}	 L5981 L5968	125kg 275lbs	142-152mm 5⅞"-6"		36	770g 1lb 11oz	ECER	22-30	L / R	N / W	1-8		S
		AvalonK2	 L5972 L5968	150kg 330lbs	115mm 4⅞⅞"		24	520g 1lb 2oz	AV	22-30	L / R				
		AvalonK2 ^{VAC}	 L5972 L5968 L5781	150kg 330lbs	122mm 4⅝⅞"		24	583g 1lb 5oz	AVAC	24-30	L / R				
		Navigator	 L5972 ✓ L5986 ✓	125kg 275lbs	95mm 3⅞⅞"		24	350g 12oz	NAV	22-30	L / R				

Spring Selection Guide Microprocessor and Hydraulic Ankles

Activity Level 2 and 4 ⁴ users who would benefit from this foot will require softer or stiffer springs as appropriate for the individual. Spring set recommendations are for trans-tibial users. For trans-femoral we suggest selecting a spring set one level lower.		User Weight													
Activity		44-52	53-59	60-68	69-77	78-88	89-100	101-116	117-125	kg		lbs			
		100-115	116-130	131-150	151-170	171-195	196-220	221-255	256-275						
3		1	2	3	4	5	6	7	8					Foot spring set	
		•		••		•••		••••						◀ Axial shock spring rate indicated as shown	
For weights above 125kg up to 150kg contact a Blatchford representative.		1		2		3		4						◀ Axial spring	

This guide is for reference only. The choice of appropriate codes remains the provider's sole responsibility to verify the accuracy of the HCPCS codes used, determine the applicability to each patient, and fulfill the medical necessity/claims documentation requirements. Blatchford assumes no responsibility or liability for the provider's actions.

Foot Shell Width Guide

Size (cm)	22	23	24	25	26	27	28	29	30
Width (mm)	76	78	80	82 (N) 88 (W)	83 (N) 91 (W)	91 (N) 99 (W)	91 (N) 100 (W)	102	105

¹Component weight shown is for size 26cm without foot shell.

²Narrow (N) and Wide (W) available for sizes 25-28 only. ³For dark tone add suffix D.

⁴Maximum user weight 100kg and always use one higher spring rate category than shown in table.

 Suitable for submersion up to 1m  Suitable for outdoor use  PDAC Approved

