

SPS TT SOCKETLESS ÖSSUR LEG ORDER FORM PACKAGE

Complete the TT Össur Leg Order Form and email to customerservice@spsco.com.*
SPS will then create and send you a quote detailing all items in the Össur Leg.

spsco.com | 800.767.7776

BILLING & SHIPPING INFORMATION

SPS Account #:	PO#	
<u>Ship To:</u>		
Company:	Contact:	
Address:	Phone:	Fax:
City/State/Zip:	Email:	

REQUIRED PATIENT INFORMATION

Patient ID:	Impact Level: High Med Low	Amputation Level: TT Symes
Weight:	lbs. K-Level: K1 K2 K3 K4	Left Right Bilat Order

1: LINERS (check one then fill in desired sizes and options)

<p>Comfort Locking</p> 	<p>Dermo Locking</p> 	<p>Iceform Locking</p> 	<p>LINER SIZE</p> <p>Standard Wave 3 mm 6 mm</p>	<p>Seal-In V HP</p> 	<p>Seal-In X5</p> 	<p>LINER SIZE</p> <p>Standard Wave</p> <p>RING SIZE</p>
<p>Comfort w/ Sleeve</p> 	<p>Dermo w/ Sleeve</p> 	<p>Iceform w/ Sleeve</p> 	<p>LINER SIZE</p> <p>Standard Wave 3 mm 6 mm</p> <p>SLEEVE SIZE</p>	<p>Seal-In V</p> 	<p>Seal-In X with Rings</p> 	<p>Seal-In X Locking with Rings</p>  <p>(Ring Options)</p> <ul style="list-style-type: none">  Classic  Volume  Grip

*This form is available in electronic form you can fill out electronically and email or print.

SPS TT SOCKETLESS ÖSSUR LEG ORDER FORM


2. SUSPENSION & SOCKET ADAPTER (check all that apply)

LOCKING OPTIONS					
 <p>Icelock 621 Ratchet & Extra Pin</p>	 <p>Icelock 651 Smooth & Extra Pin</p>	 <p>Icelock 562 Hybrid</p>	 <p>Icelock 600XM</p>	 <p>Icelock 211 Clutch & Extra Pin Icelock 214 4-Hole Clutch & Extra Pin</p>	 <p>Icelock 234 Lanyard</p>
Works With					
 <p>Icelock 672 Male Pyramid Ti Icelock 673 Male Pyramid Al</p>	 <p>Icelock 674 4-Hole Adapter Al Icelock 675 4-Hole Adapter Ti</p>				
EXPULSION OPTIONS			UNITY ELEVATED VACUUM OPTIONS		
 <p>Icelock 544 Expulsion Kit</p>	 <p>Icelock 551 Expulsion Valve</p>	 <p>Unity Valve TT</p>	 <p>Icelock 544 Unity Plate</p>		
 <p>Icelock 544 Expulsion Valve Kit for sleeves</p>	Works With				
	 <p>Icelock 544 Socket Adapter</p>	 <p>3-Prong Socket Adapter 4-Prong Socket Adapter</p>			

3: ENDOSKELETAL COMPONENTS (check all that apply)
















 <p>4-HOLE ADAPTERS</p> <ul style="list-style-type: none"> 4-Hole Male 4-Hole Female 4-Hole Male w/ Rotation 4-Hole Female w/ Rotation 4-Hole Male w/ 8mm Ax Offset 	 <p>DOUBLE ADAPTERS</p> <ul style="list-style-type: none"> Female Double Adapter 32mm Female Double Adapter 45mm Female Double Adapter 60mm Female Double Adapter 75mm Offset 	 <p>TUBE CLAMPS</p> <ul style="list-style-type: none"> Male Tube Clamp Female Tube Clamp 4-Hole Tube Clamp
 <p>4-Hole Female Pyramid 20/20 Offset</p>  <p>4-Hole Female Pyramid 20/20 Offset, 10 degree, Right</p>  <p>4-Hole Female Pyramid 20/20 Offset, 10 degree, Left</p>	 <p>PYLONS</p> <ul style="list-style-type: none"> Height Adjustable Standard Height Adjustable Long Pylon Al, 220lb Limit Female Short Female Kit Short Pylon Ti Waterproof, 365lb Limit Female Long Female Kit Long 	 <p>SINGLE ADAPTERS</p> <ul style="list-style-type: none"> Male Single Adapter Short Male Single Adapter Long Female Single Adapter Short Female Single Adapter Long <p>Other:</p>
 <p>INSERTS FOR PRONG</p> <ul style="list-style-type: none"> Male Insert for Prong Female Insert for Prong LP Female Inserts for Prong 		

Össur may select different components to fit your dimensions if necessary. If you do not want Össur to make any changes, check this box:

 Waterproof rated Össur products provide permanent protection against harmful ingress of fresh, salt or chlorinated water, even after submersion

SPS TT SOCKETLESS ÖSSUR LEG ORDER FORM

4: FOOT: WITH OR WITHOUT UNITY (check one and fill out the options below)

FOOT OPTIONS:		Foot Size:	cm.	Category (1-9)	Left	Right	Foot Shell:	Beige	Brown														
				Suggested L-Codes†					Suggested L-Codes†														
	Balance Foot S with Torsion with Unity	5972, 5986 5972, 5984, 5988 5781*				K2 Sensation with DP Flexion with Unity			5972, 5986 5972, 5968 5781*														
	Balance J with Unity	5976 5781*				Assure with Unity			5981 5781*														
	Talux	5981‡, 5986‡				Vari-Flex with Unity			5981‡ 5781*														
	Pro-Flex Pivot with Unity	See Össur reimbursement guide				Pro-Flex LP Pro-Flex LP Torsion with Unity			5981, 5986 5981, 5984, 5988 5781*														
	Pro-Flex LP Align	5981, 5986, 5990				Proprio Foot with Unity			5973‡ 5781*														
	Pro-Flex XC Pro-Flex XC Torsion with Unity	5981‡ 5987‡, 5984‡ 5781*				ReFlex Rotate with Unity			5987‡, 5984‡ 5781*														
	ReFlex Shock with Unity	5987‡ 5781*				Torsion Shock Adapter with Male Pyramid Adapter with Female Pyramid Adapter			5984, 5988														
	Vari-Flex Modular with Male Pyramid	5980‡			Desired build height (mm): With foot cover on. No return or exchange after foot is cut. <table border="1"> <thead> <tr> <th rowspan="2">Foot Size</th> <th colspan="2">Build Height</th> </tr> <tr> <th>Min</th> <th>Max</th> </tr> </thead> <tbody> <tr> <td>22-24cm</td> <td>188mm</td> <td>326mm</td> </tr> <tr> <td>25-27cm</td> <td>188mm</td> <td>383mm</td> </tr> <tr> <td>28-30cm</td> <td>188mm</td> <td>400mm</td> </tr> </tbody> </table>					Foot Size	Build Height		Min	Max	22-24cm	188mm	326mm	25-27cm	188mm	383mm	28-30cm	188mm	400mm
Foot Size	Build Height																						
	Min	Max																					
22-24cm	188mm	326mm																					
25-27cm	188mm	383mm																					
28-30cm	188mm	400mm																					

*Unity code added to other codes, e.g. Proprio Foot with Unity: 5973, 5781.

†The responsibility for accurate coding lies solely with the healthcare provider, Össur assumes no responsibility or liability for the provider's coding decisions.

‡PDAC approved.

CLEAR FORM

4 of 4