



DURR-FILLAUER MEDICAL, INC.

ORTHOPEDIC DIVISION

P. O. Box 5189 □ Chattanooga, Tennessee 37406 □ (615) 624-0946 □ (800) 251-6398 □ (800) 572-7650 (TN WATS)
Telex 558422 □ Cable DFORTHO

O U R REF:
YOUR REF:

Page ~~003~~ 1/4

SPS Internal # **99847**
Product I.D.:
PELITE CONES

MATERIAL SAFETY DATA SHEET FOR PE-LITE A-8, B-4, A-20

=====

MANUFACTURER'S NAME	INOUE MTP CO., LTD.
EMERGENCY TELEPHONE NO.	(052) 251-9666
ADDRESS	3-11, Sakae 5-Chome, Naka-Ku, Nagoya 460
CHEMICAL NAME AND SYNONYMS	Polyethylene Foam
CHEMICAL FAMILY	Olefins



DURR-FILLAUER MEDICAL, INC.
ORTHOPEDIC DIVISION

P. O. Box 5189 □ Chattanooga, Tennessee 37406 □ (615) 624-0946 □ (800) 251-6398 □ (800) 572-7650 (TN WATS)
Telex 558422 □ Cable DFORTHO

O U R REF:

YOUR REF:

Page 1 2/4

1. PRODUCT IDENTIFICATION

	A-8	B-4	A-20
CHEMICAL NAME	Polyethylene Foam	Polyethylene Foam	Ethylene-Vinylacetate Copolymer Foam
CHEMICAL FAMILY	Olefins	Olefins	Olefins
FORMULA	$(CH_2)_n$	$(CH_2)_n$	$\begin{array}{c} COCH_3 \\ \\ (CH_2)_n + (CH-CH)_n \end{array}$
MOLECULAR WEIGHT	$> 10^4$	$> 10^4$	$> 10^4$
TRADE NAME	PE-LITE A-8	PE-LITE B-4	PE-LITE A-20



DURA-FILLAUER MEDICAL, INC.
ORTHOPEDIC DIVISION

P. O. Box 5189 □ Chattanooga, Tennessee 37406 □ (615) 624-0946 □ (800) 251-6398 □ (800) 572-7650 (TN WATS)
Telex 558422 □ Cable DFORTH0

O U R REF:

YOUR REF:

Page 3/4

2. PHYSICAL DATA

	A-8	B-4	A-20
BOILING POINT	NA	NA	NA
VAPOR PRESSURE	NA	NA	NA
VAPOR DENSITY	NA	NA	NA
SOLUBILITY IN WATER % BY WEIGHT	NA	NA	NA
MELTING POINT	> 150°C	> 150°C	> 140°C
SPECIFIC GRAVITY (H O = 1)	0.07	0.03	0.16
PERCENT VOLATILE BY VOLUME (%)	NA	NA	NA
EVAPORATION RATE	NA	NA	NA
APPEARANCE AND ODOR	Closed Cell Odor like Amine	Closed Cell	Closed Cell



DURR-FILLAUER MEDICAL, INC.
ORTHOPEDIC DIVISION

P. O. Box 5189 □ Chattanooga, Tennessee 37406 □ (615) 624-0946 □ (800) 251-6398 □ (800) 572-7650 (TN WATS)
Telex 558422 □ Cable DFORTHO

O U R REF:
YOUR REF:

Page 4/4

3. FIRE AND EXPROSION HAZARD DATA

	A-8		B-4	A-20
FLASH POINT	> 200°C		> 200°C	> 270°C
AUTOIGNITION TEMPERATURE	> 400°C		> 400°C	> 450°C
FLAMABLE LIMITS IN AIR PERCENT BY VOLUME	LOWER	NA	NA	NA
	UPPER	NA	NA	NA
EXTINGUISHING MEDIA	Water, Carbon Dioxide or dry chemical		Water, Carbon Dioxide or dry chemical	Water, Carbon Dioxide

4. HEALTH HAZARD DATA

Passed Food Hygiene Test
Notification No. 370 of The Ministry of Health and Welfare



DURR-FILLAUER MEDICAL, INC.
ORTHOPEDIC DIVISION

P. O. Box 5189 □ Chattanooga, Tennessee 37406 □ (615) 624-0946 □ (800) 251-6398 □ (800) 572-7650 (TN WATS)
Telex 558422 □ Cable DFORTHO

O U R REF:
YOUR REF:

Page 5/5

5. REACTIVITY DATA

	A-8	B-4	A-20
STABILITY	Stable		
MATERIALS TO AVOID	Strong Acid, Strong Solvent (Toluene Gasolin, etc.)		
HAZARDOUS DECOMPOSITION PRODUCTS	Carbon Monoxide, Carbon Dioxide		
HAZARDOUS POLYMERIZATION	will not occur		
CONDITIONS TO AVOID	Ultraviolet Rays, High Temperature		

6. SPILL OR LEAK PROCEDURES

Waste Disposal Method: Burn

7. SPECIAL PROTECTION INFORMATION

Respiratory Protection: None Required

Ventilation : None Required

8. SPECIAL PRECAUTION

None